
MORBARK® 6600 TRACK WOOD HOG

FEATURES

- Variable speed infeed system consists of one 36"
 (91.44 cm) diameter top compression feed roll with internal drive and a 12'6" long x 64" (3.81 m x 162 cm) wide live floor equipped with five strands of WDH-120 chain in a staggered configuration with 4'7" (1.3 m) long hydraulically operated folding infeed extension
- » 42" x 66 %" (106.7 cm x 169 cm) Hammermill system constructed of heavy-duty 28" (71.12 cm) diameter rotor, (18) 1%" (46.67 cm) thick two-piece laser-cut rotor plates keyed on a 9" (22.86 cm) diameter shaft with 5%" (13.17 cm) bearings and eight 2½" (6.35 cm) hammer retaining rods. Hammermill pattern has (18) 2¼" (5.71 cm) balanced forged steel hammers, (18) 3%" (9.2 cm) wide double-edged replaceable inserts and 18 forged rakers



- » Automatic reversing fan system
- » Dust suppression system
- » Hydraulically operated debris containment door
- » Discharge system consists of a hydraulically driven, horizontal 48" wide x 19' (121.92 cm x 5.79 m) long aggregate belly belt conveyor discharging onto a 40" (101.6 cm) wide stacking conveyor with hydraulic fold for transport
- » Remote control with tethered back-up system
- » Magnetized end pulley with collecting slide tray for ferrous metal removal
- » 11-HP (8.2 kW) air compressor with lockable enclosure

OPTIONS

- » 330L Caterpillar Undercarriage
- » 14-knife chipper drum assembly
- » Hydraulic rod puller



Morbark Integrated Control System (MICS)

Internal Planetary Drive Feed System

Externally Adjustable Break-away Torque Limiter







SPECIFICATIONS	US	METRIC
Length (transport)	44'9"	13.64 m
Length (operating)	67'1"	20.45 m
Height (transport)	11'11"	3.63 m
Height (operating)	18'6"	5.69 m
Width	11'11"	3.63 m
Gross Weight (approx.)	109,120 lbs	49,500 kg
Engine	CAT	
Horsepower	1,125 to 1,200 HP	838 to 894 kW
Fuel Capacity (tank)	390 gallons	1,478 litres
Hydraulic Oil	335 gallons	1,268 litres
Infeed Opening	66" x 50"	167 cm x 127 cm
Tracks	SS40 Strickland Undercarriage	

