

MORBARK® 950 TUB GRINDER

FEATURES

- » Two 12" (30.48 cm) diameter augers discharge onto a 28" (71.12 cm) x 12' (3.66 m) upright discharge conveyor
- » Tub has 8'4" (2.54 m) diameter opening across the top, 6'6" (1.98 m) diameter inside base, and 44" (111.76 cm) deep walls constructed of ¼" (.63 cm) reinforced steel plate, floor constructed of ¼" (.63 cm) thick T-1 wear-resistant steel
- » Tub supported by 5 rubber tire guide rolls
- » 22 ½" (57.15 cm) x 32 ½" (82.55 cm) hammermill system constructed of heavy-duty 16" (40.64 cm) diameter laser-cut rotor, (13) 1 ½" (34 cm) thick 2-piece laser-cut rotor plates to ensure precision and enforce steel strength. The plates are keyed on a 4 ½" (11.43 cm) diameter rotor shaft with 2 ⅝" (7.46 cm) bearings direct driven at engine RPM and eight 1 ¼" (3 cm) hammer retaining rods
- » Tub is equipped with hydraulic augers that allows the operator to quickly remove product from beneath the mill. During material surges, pressure sensors automatically slow tub rotation to prevent plugging
- » Magnetized end pulley for discharge conveyor, complete with collecting slide tray for ferrous metal removal
- » Remote control with tethered back-up system
- » Dust suppression system
- » 11-HP (8.2 kW) air compressor

OPTIONS

- » Fifth wheel towing arrangement with single axle
- » 1/3 tub cover
- » Dual tub slide tray assembly



Laser-cut, factory-balanced hammermills with forged hammers

The full breakaway torque limiter system protects the engine and clutch

Hydraulically tilt the tub for easy access to grates and anvil



SPECIFICATIONS

US

METRIC

Length (transport)	22'	6.7 m
Length (operating)	29'5"	8.97 m
Height (transport)	12'5"	3.78 m
Width	8'4"	2.54 m
Gross Weight	12,750 lbs	5,785 kg
Engine	CAT	
Horsepower	202 HP	150 kW
Fuel Capacity (tank)	59 gallons	223 litres
Hydraulic Oil	50 gallons	189 litres
Screen Area	1,612 sq in	10,400 sq cm
Tires	LT245/75R16.0	
Towing arrangement	Pintle hitch	
Brakes	Electric	
Tracks (Option)	312B Caterpillar Undercarriage	



MORBARK®

www.morbark.com

800.831.0042

SPECIFICATIONS MAY VARY WITH EQUIPMENT OPTIONS

4/20/18